

Security Defence Systems

Plot No. 50, DIC, Industrial Area, Baddi, Solan (H.P)

Web: www.sdschd.com

Email: rajeshmkt@yahoo.com raghavendersahdev@gmail.com

Phone: 0172-2632668 Mobile: 09814014406 Fax: 0172-2633668

BOLLARD



MODEL: BOLLARD

We offer extremely high quality automatic bollards that meet the relevant standards in their range of impact resistance in each category. Our Bollards will be secured in the housing firmly when raised or lowered.

All Bollards will have fluorescent strips and LEDs on the periphery for visibility from a distance. Manual and automatic Bollards consume less space and disappear in the ground compared to road blockers. State-of-the-art facilities easy installation, maintenance and replacement.

Salient Features

- Offered in hydraulic, electric and pneumatic.
- Raising and lowering time is from 3-6 seconds.
- Height ranges from 500-900 mm.
- Diameters range from 100-400 mm.
- Interface with traffic signal system or independent controlling stations.
- Can be operated over 300-800 cycles per day.
- Available in stainless steel and mild steel.
- Choice of standard colors for weather resistance painting.
- Controlling options: manual remote pendent, RFID and proximity sensor based.
- Meeting the specifications of k2, k4 & k6.
- Wide range of accessories for different environments.
- Custom built bollards for specific requirements.
- Optional elements for power failures.