



# Security Defence Systems

Plot No. 50, DIC, Industrial Area , Baddi, Solan (H.P)

Web: [www.sdschd.com](http://www.sdschd.com)

Email: [rajeshmkt@yahoo.com](mailto:rajeshmkt@yahoo.com)

Phone: 0172-2632668

[raghavendersahdev@gmail.com](mailto:raghavendersahdev@gmail.com)

Mobile: 09814014406

Fax: 0172-2633668

## D-2055 LED (Portable DFMD)



*MODEL : D-2055 LED (Portable DFMD)*

### Construction

Door Frame metal detector detects ferrous, non-ferrous metals and their alloys. It detects a pistol even when concealed in ferrite rods in all six possible orientations at all speeds. Two door frames can be placed near by without affecting performance. Door frame is made up of flexible cable housed in telescopic extendable PVC pipe frame with clutches for quick release and locking systems is contained in the canvas carrying bag. The pipes can be joined fixed to form a door frame by releasing/tightening the clutch.

The control unit is housed in a briefcase. Wooden ramp for protection of coils and two wooden legs for stability of the frame are provided.

The entire system can be assembled in less than 5 minutes to form an archway door frame metal detectors. It has plug in card systems and IR sensors to avoid outside movement alarms.

### Technical Features



# Security Defence Systems

Plot No. 50, DIC, Industrial Area , Baddi, Solan (H.P)

Web: [www.sdschd.com](http://www.sdschd.com)

Email: [rajeshmkt@yahoo.com](mailto:rajeshmkt@yahoo.com)

Phone: 0172-2632668

[raghavendersahdev@gmail.com](mailto:raghavendersahdev@gmail.com)

Mobile: 09814014406

Fax: 0172-2633668

Technology	Microcontroller
Zone	Single
Tuning	Auto Setting
Visual display	LED
Audio	Four Tone
Counter	5 digit IN, OUT & NETIN
Sensor	IR
Sensitivity Level	0 to 9
Indicator	Low battery & WALK/STOP
Threshold	0 to 5
UPS	>80 hrs
Power	230V AC +/- 15%, 50Hz
Battery	6V rechargeable and dry batteries
SMPS	90V to 270V
Operating temperature	-20°C to +55°C