

Security Defence Systems

Plot No. 50, DIC, Industrial Area , Baddi, Solan (H.P)

Web: www.sdschd.com

Email: rajeshmkt@yahoo.com raghavendersahdev@gmail.com
 Phone:
 0172-2632668

 Mobile:
 09814014406

 Fax:
 0172-2633668

LETTER BOMB DETECTOR LBD-II LED



MODEL : LBD-II LED

Technology:	Analog Signal Processing
Power:	Works on AC as well as DC
Dimensions:	480 x 410 x 290 mm.
Weight:	less than 12 kg.
Detection:	 Detects ferrous and non-ferrous metals with high sensitivity. Detects almost all DIP integrated circuits, smallest of button cells, detonators used in letter bombs. Its rough and tough and easy to use. Scans up to a small mail packet of 38mm thickness x 270mm width.
Operation :	 No Calibration needed. Visual and audio alarm. Integrated battery backup with built-in charger
Charger:	It has low battery indicator by way of visual indication and long delay beeper.
Sensitivity:	Minimum watch cell size of 6mm diameter x 2.5mm thickness of any metal or alloy.
Indications:	Sharp Beep through buzzer.
Service Manual:	Complete with technical details, circuit-diagram, calibration & test method. Test sample for checking the detector provided.